

Datasheet - NDTSW

Command and signalling devices / Push buttons and pilot lights - "N" Program / NDT - Push button



(Minor differences between the printed image and the original product may exist!)

Ordering details

Product type description	NDTSW
Article number	101163559
EAN code	4250116200009

Approval

Approval



Global Properties

Product name	NDT - Push button
Standards	IEC/EN 60947-1, EN 60947-5-1
Compliance with the Directives (Y/N)	No
Suitable for safety functions (Y/N)	No
Mounting	mounting flange EFM
Materials	
- Material of the operators	ABS
- Material of the front ring	ABS, Chromium-plated
Design	Embeddable button - Front plate mounting
Form	Round
Color	
- Colour of the operating element	■ Black

- Colour of the bellows	<input type="checkbox"/> White
- Colour of the front ring	<input checked="" type="checkbox"/> Silver
Weight	25 g
Manner of using	
Can be illuminated (Y/N)	No

Mechanical data

Actuating stroke	5 mm
Latching (Y/N)	No
Unlocking type	without
Probing possible (Y/N)	Yes
mounting flange available (Y/N)	Yes
Front plate thickness	
- min. front plate thickness	1.5 mm
- max. front plate thickness	6 mm
Tightening torque for fixing screws	0,6 Nm

Ambient conditions

Ambient temperature	
- Min. environmental temperature	-25 °C
- Max. environmental temperature	+80 °C
Storage and transport temperature	
- Min. Storage and transport temperature	-
- Max. Storage and transport temperature	-
Fully insulated (Y/N)	Yes
Sealing type	membrane, lip seal
Protection type IP	IP67, IP69K



LED switching conditions display

With integrated LED (Y/N)	No
---------------------------	----

Dimensions

Dimensions	
- Height	11 mm
- diameters for the actuating heads	Ø 44.5 mm
- Hole, diameter	22.3 mm + 0,4 mm
Spacing	50 x 50 mm

Images



Application

System components

Accessories

101014388 - EFM



NSK - Protective collar against unintentional contact

- for pushbuttons and illuminated pushbuttons



contact element

contact element EF - (N)

- Flat plug-in connector
- Mounting flange position 2
- 21-22 (Contact labelling)



K.A. Schmersal GmbH, Möddinghofe 30, D-42279 Wuppertal

The data and values have been checked thoroughly. Technical modifications and errors excepted.

Generiert am 02.11.2012 - 15:32:12h Kasbase 2.2.2.F DBI

Image

Image

et=sS