

Auxiliary actuator for optional use with Standard Size Enclosed terminal
Micro Switches with cowl-protected spring plunger actuators MS-7 & MBC1

Actuator : Metal lever with free-running plastic roller

Adjustable through 145°. M4 hexagonal head adjustment lock.

Frame : Double plate type which straddles the switch, in plated mild steel.

Mounting : Two M3.5 screws with washers and nuts are provided.


The 35 mm screws are long enough not only to fix

the actuator to the switch but also the complete assembly to the application.

Lever Ratio : 3.6 : 1

Note : The reference LR1 covers the auxiliary actuator and hardware only. The switch should be ordered separately.

CAT No. : LR1H

CAT No. : LR1H						
		01	ISS. DATE	MODIFICATION SIGN		
TOLERANCES UNLESS OTHERWISE SPECIFIED ± 0.1	ACTUATOR LR1H FOR MICRO SWITCHES MS-7 & MBC1			DIMENSIONS IN M		
					DATE	SIGN
				DESIGN	21.01.03	W. B. H.
				DRAWN	21.01.03	K. K.
				CHKD.		
				APPD.		
SCALE ~				DRG. NO.		
		LR1CU-001. A4				
		ESSEN DEINKI 22, INDUSTRIAL AREA, PHASE II CHANDIGARH - 160002				
		SHEET 01 OF 01				