



AZ 07 KT 08106

- Single-conductor entry with strain relief
- Thermoplastic enclosure
- Contact pin in actuator bridge
- 1 Actuating planes
- Protection class IP20
- transparent cover
- fixing screws M4 undetachable, captive
- Fitting dimensions suitable for AZ 06x
- Self-cleaning through the frictional movement of the contact bridges
- Enclosure with mounting slots

Data

Ordering data

Product type description	AZ 07 KT 08106
Article number (order number)	101195820
EAN (European Article Number)	4030661362854
eCl@ss number, version 12.0	27-27-06-10
eCl@ss number, version 11.0	27-27-06-10
eCl@ss number, version 9.0	27-27-06-10
ETIM number, version 7.0	EC002592
ETIM number, version 6.0	EC002592

General data

Standards	EN 81-20 EN 81-50
Housing material	Plastic, glass-fibre reinforced thermoplastic, self-extinguishing
Material of the housing cover	transparent thermoplastic, self-extinguishing
Gross weight	30 g

General data - Features

Suitable for elevators	Yes
Number of safety contacts	1

Mechanical data

Actuating panels	1
Mechanical life, minimum	1,000,000 Operations
Actuating stroke	7 mm
Actuating force, approx.	1.6 N
Mounting	Fine-adjustment through slotted holes

Mechanical data - Connection technique

Cable entry	Single-conductor entry with strain relief
Termination	Screw terminals M20 x 1.5

Mechanical data - Dimensions

Width	72 mm
Height	22 mm
Depth	19 mm

Ambient conditions

Degree of protection	IP20
Ambient temperature	-15 ... +70 °C
Relative humidity, maximum	95 %
Note (Relative humidity)	non-condensing

Ambient conditions - Insulation values

Rated insulation voltage U_i	500 V
--------------------------------	-------

Schmersal Ltd., Sparrowhawk Close, WR14 1GL Malvern

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 25/03/2024, 16:01