



## AZ 14-1 KU CONTACT

- Actuation bottom
- Thermoplastic enclosure
- Contact pin in actuator bridge
- 2 actuating planes
- Protection class IP20
- Self-cleaning through the frictional movement of the contact bridges

## Data

### Ordering data

Product type description	AZ 14-1 KU CONTACT
Article number (order number)	101157701
EAN (European Article Number)	4030661180953
eCl@ss number, version 12.0	27-27-06-12
eCl@ss number, version 11.0	27-27-06-05
eCl@ss number, version 9.0	27-27-06-05
ETIM number, version 7.0	EC001487
ETIM number, version 6.0	EC001487

### Approvals - Standards

Certificates	TÜV CCC
--------------	------------

### General data

Standards	EN 81-20 EN 81-50
Housing material	Plastic, glass-fibre reinforced thermoplastic, self-extinguishing

Material of the housing cover	thermoplastic, self-extinguishing
Gross weight	40 g

### General data - Features

Suitable for elevators	Yes
Number of safety contacts	1

### Mechanical data

Actuating panels	1. bottom
Mechanical life, minimum	1,000,000 Operations
Actuating stroke	7 mm
Actuating force, approx.	2.2 N
Mounting	Round holes

### Mechanical data - Connection technique

Cable entry	Wiring compartment
Termination	Screw terminals M20 x 1.5
Notes	M4, with self-opening clamping plates

### Mechanical data - Dimensions

Width	44 mm
Height	61 mm
Depth	19 mm

### Ambient conditions

Degree of protection	IP20
Ambient temperature	-30 ... +70 °C

### Ambient conditions - Insulation values



The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 25/03/2024, 17:23